

#WD-506  
PLANIPATCH



## PLANIPATCH & PLANIPATCH PLUS

Planipatch® is an ultra fast drying, self curing, polymer-modified cement-based patching compound for filling and leveling joints, voids, holes and cracks in wood and concrete subfloors. Combined with Planipatch™ Plus for improved adhesion and flexibility, Planipatch® is used to prepare surfaces for application of Weatherdek membranes.



### PLANIPATCH®:

- Fast setting
- Polymer-modified
- Easy to apply

### PLANIPATCH PLUS™:

- Superior adhesion
- Improves flexibility & strength

### APPLICATION:

- 'Diluted' - 1 part Planipatch Plus™ to 3 parts water - mix with Planipatch®
- 'Full-Strength' - roughly 1 gal Planipatch Plus™ per 20 lbs Planipatch®
- Recommended minimum application temperature 10°C (50°F)

### PACKAGING:

- Planipatch® - 22 lb bag
- Planipatch Plus™ - 1 gal (3.79L) Jug

### CAUTION:

- Refer to SDS Sheet before use

**LINKS:** - [Weatherdek Installation Guide](#) - [PLANIPATCH® SDS](#) - [PLANIPATCH PLUS™ SDS](#)

For further information regarding Weatherdek products please contact:  
ADS Weatherdek Canada Ltd. at: [www.weatherdek.com](http://www.weatherdek.com) or 1-800-667-2596